

## Description

Nexus ATF Dexron III is formulated with special additive packages combined with HVI (High Viscosity Index) base stocks to provide superior friction characteristics. Anti-corrosion, anti-rust and anti-foam formula.

Standards                      DEXRON III

## Applications

Drain interval                      : according to manufacturer's recommendations and tuned to your own use.

## Benefits

- Outstanding thermal and oxidation stability for consistent transmission performance
- Compatible with all seal material to prevent oil leaking
- Formulated with selected base stocks to prevent sludge build-up
- Good lubricity performance to boost transmission lifespan

	NEXUS ATF DEXRON III
Kinematic Viscosity @ 40°C/104°F, ASTM D 445	37.4
Kinematic Viscosity @ 100°C/212°F, ASTM D 445	7.34
Viscosity Index, ASTM D2270/ISO 2909	>120
Pour Point, ASTM D97, °C/°F	-52.5/-913
Flash Point – open cup method, ASTM D92/ISO 2592, °C/°F	220 / 428

\*Subject to usual manufacturing tolerances

**Nexus ATF DEXRON III**

20 Mar 2024

Nexus, the Nexus logo, and related marks are trademarks of Nexus Limited, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Nexus or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.