

Product Data Sheet

Description

Nexus D-Moly Lube is a high lubricity dry molybdenum that adheres to most surfaces with minimum surface preparation. Designed to dry rapidly at room temperature to provide clean, long-wearing lubrication. It can withstand operational temperature range up to 454°C/850°F. **Nexus D-Moly Lube** is also conductive and may be used where lubrication and electrical properties are both required

Applications

- Textile stenter frames
- Automotive and industrial gaskets
- Bearings
- Chains
- Springs
- Locks
- Bushings

Benefits

- Excellent conductivity
- Dries rapidly at room temperature
- Works up to 454°C/538° intermittently

Product Data Sheet

	D-MOLY LUBE
Appearance	Dull black solid film
Odor	Mild solvent
Temperature range, °C	-40 to 454
Coefficient of friction, ASTM D4518	0.23
Flash Point, °F	<0

*Subject to usual manufacturing tolerances

Nexus D-Moly Lube

20 Mar 2024

Nexus, the Nexus logo, and related marks are trademarks of Nexus Limited, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Nexus or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.