

### **Description**

**Nexus EP Gear Oil** is a high-performance extreme pressure lubricant formulated with high-quality base oils and advanced additive technology to provide reliable protection under severe operating conditions.

The product is designed to protect gear systems operating at elevated temperatures, high speeds, and under heavy loads, including shock loading conditions. Its robust formulation helps prevent scuffing, scoring, corrosion, and pitting, ensuring long component life and dependable operation in high torque and high horsepower applications.

### **Applications**

Nexus EP Gear Oil is recommended for lubrication of industrial gear systems operating under moderate to severe conditions, including:

- **Enclosed Industrial Gear Drives**  
Suitable for spur, helical, bevel, and planetary gear systems requiring high-performance lubrication.
- **Heavy-Duty Gearboxes**  
Recommended for equipment operating under high load, shock load, or continuous operation.
- **High-Temperature Applications**  
Ideal for systems where reduced operating temperature and enhanced thermal stability are required.
- **Circulating and Splash Lubrication Systems**  
Compatible with both splash and forced lubrication systems.
- **Bearings and Ancillary Components**  
Suitable for lubricating bearings associated with gear systems where EP performance is required.
- **Applications Requiring Extended Oil Life**  
Particularly suited for operations where extended maintenance intervals and reduced downtime are critical.
- **Textile Machinery**  
Recommended for gearboxes in weaving, spinning, and finishing equipment requiring reliable EP protection under continuous operation.

## Product Data Sheet

### Benefits

- **Reliable Extreme Pressure Protection**  
Provides effective protection against scuffing, scoring, and pitting under heavy and shock loading conditions.
- **Consistent Performance in Continuous Operation**  
Maintains stable lubrication performance in equipment running 24/7, such as textile machinery.
- **Suitable for Textile Gear Systems**  
Ensures reliable protection for gearboxes in weaving, spinning, and finishing machines operating at moderate speeds and loads.
- **Robust Wear Protection**  
Forms a protective lubricating film to reduce wear on gears and bearings, extending component life.
- **Good Load Carrying Capability**  
Handles moderate to high loads effectively across a wide range of industrial applications.
- **Corrosion Protection**  
Protects metal surfaces from rust and corrosion during operation and idle periods.
- **Operational Stability in Harsh Environments**  
Performs reliably in dusty, humid, and high-contamination environments such as textile and general manufacturing plants.
- **Balanced Oxidation Resistance**  
Provides adequate resistance to oxidation for standard service intervals.
- **Cost-Effective Maintenance**  
Offers dependable protection with economical operating cost, ideal for large-scale plant usage.

# Product Data Sheet

	EP68	EP100	EP150	EP220	EP320	EP460	EP680
ISO Viscosity Grade, ASTM D 2442	68	100	150	220	320	460	680
Density @ 20°C	0.865	0.875	0.8	0.879	0.9	0.915	0.922
Kinematic Viscosity @ 40°C/104°F, ASTM D 445	68	100	150	241.7	320	460	680
Kinematic Viscosity @ 100°C/212°F, ASTM D 445	8.5	10.5	13.5	21.75	23	30	40
Viscosity Index, ASTM D 2270	>110	>110	>110	>110	>110	>110	>110
Flash Point, ASTM D 92, COC, °C/°F	220/428	220/428	220/428	>220/428	>220/428	>220/428	>220/428
Fire Point, ASTM D 92, COC, °C/°F	>250/482	>250/482	>250/482	>250/482	>250/482	>250/482	>250/482
Pour Point, ASTM D 97, °C/°F	-9/15.8	-9/15.8	-9/15.8	-15/5	-9/15.8	-9/15.8	-9/15.8
Scardiameter, Fourball, ASTM D4172-20, mm	0.45	0.5	0.5	0.5	0.5	0.5	0.5

\*Subject to usual manufacturing tolerances

### Nexus Extreme Pressure Gear Oil

20 Mar 2024

Nexus, the Nexus logo, and related marks are trademarks of Nexus Limited, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Nexus or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.