

Description

Nexus Hemera is a high-performance engine oil formulated with carefully selected base oils and advanced additive technology to deliver outstanding protection against wear and oxidation. It ensures reliable lubrication and helps maintain optimal engine performance under demanding operating conditions.

Designed to operate across a wide temperature range, Nexus Hemera provides consistent viscosity performance, enabling smooth engine operation during both cold starts and high-temperature service.

Nexus Hemera meets the requirements of the **American Petroleum Institute (API) CH-4** specification, making it suitable for a wide range of diesel engine applications.

Applications

Nexus Hemera is recommended for:

- Heavy-duty diesel engines in trucks, buses, and commercial vehicles
- Off-highway equipment, including construction and mining machinery
- Agricultural equipment operating under varying load conditions
- Stationary diesel engines and generators
- Engines requiring API CH-4 performance level

Benefits

- **Excellent Wear Protection**
Helps extend engine life by reducing component wear
- **Outstanding Oxidation Stability**
Minimizes oil degradation and deposit formation
- **Wide Temperature Performance**
Ensures reliable lubrication in both low and high temperatures
- **Engine Cleanliness**
Helps control sludge and deposits for cleaner engine operation

Product Data Sheet

- **Reliable Performance Under Load**
Maintains lubrication film strength under heavy-duty conditions
- **Extended Service Capability**
Supports longer drain intervals under proper operating conditions

Property	Typical Value
Viscosity Grade, SAE J 300	15W-40
Kinematic Viscosity @ 40°C/104°F, ASTM D445	95 – 115
Kinematic Viscosity @ 100°C/212°F, ASTM D445	13.5 – 15.0
Viscosity Index, ASTM D2270/ISO 2909	110 – 130
Pour Point, ASTM D97, °C/°F	-18 / 0
Flash Point – open cup method, ASTM D92/ISO 2592, °C/°F	220 – 240 / 428 – 464
Total Base Number (TBN), ASTM D2896, mgKOH/g	9.0 – 11.0

*Subject to usual manufacturing tolerances

Nexus Hemera

20 Mar 2024

Nexus, the Nexus logo, and related marks are trademarks of Nexus Limited, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Nexus or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.