

## Description

**Nexus LS High Temperature Chain Oils** are specially formulated for the lubrication of chains operating under high temperature and heavy load conditions. The advanced formulation delivers excellent load-carrying capacity and anti-wear performance, ensuring reliable protection of chain components.

These oils are designed to operate cleanly, forming virtually no lacquer or harmful residues, even at elevated temperatures, thereby helping to maintain system cleanliness and efficiency.

**Nexus LS Series** are engineered for a wide range of industrial chain applications and are suitable for use across various industries. The products are available in multiple viscosity grades to meet specific equipment and operating requirements.

## Applications

Nexus LS Series is recommended for lubrication of chains operating under high-temperature and severe conditions, including:

- **Oven and Furnace Chains**  
Suitable for bakery ovens, paint curing ovens, and industrial furnaces operating at elevated temperatures.
- **Conveyor Chains**  
Used in drying, curing, and heat treatment processes where continuous operation is required.
- **Textile and Fiber Processing Chains**  
Applicable for stenter frames and other high-temperature textile machinery.
- **Wood, Paper, and Packaging Industry**  
Ideal for chains in drying and processing sections.
- **General Industrial Chain Applications**  
Recommended as a multi-service lubricant for plant-wide use across various chain systems.
- **Worn Chain Systems**  
Effective in chains with increased clearances, helping maintain lubrication film and reduce further wear.

## Product Data Sheet

### Benefits

- **Superior Clean Operation**  
Special formulation minimizes lacquer, carbon, and residue formation, keeping chains clean even under prolonged high-temperature exposure.
- **High Load Carrying Capability**  
Designed to withstand heavy loads and shock loading, ensuring reliable protection in demanding industrial environments.
- **Enhanced Component Reliability**  
Maintains smooth chain movement and reduces the risk of chain stiffening or seizure.
- **Reduced Maintenance Intervention**  
Clean-running performance helps reduce cleaning frequency and maintenance downtime.
- **Thermal Stability Under Severe Conditions**  
Maintains consistent lubrication performance under continuous high-temperature operation.
- **Improved Equipment Uptime**  
Reliable lubrication reduces unexpected failures and supports uninterrupted production.
- **Controlled Consumption**  
Optimized formulation helps reduce oil consumption under high-temperature conditions.
- **Flexible Application Range**  
Available in various viscosity grades to accommodate different chain designs and operating requirements.

## Product Data Sheet

	NEXUS LS 150	NEXUS LS 220	NEXUS LS 320
ISO Viscosity Grade, ASTM D 2442	150	220	320
Specific Gravity, ASTM D 1298 @ 15.6°C/60°F	0.8768	0.8834	0.918
Kinematic Viscosity @ 40°C/104°F, ASTM D 445	165.4	211.9	323.2
Kinematic Viscosity @ 100°C/212°F, ASTM D 445	16.64	21.18	25.72
Viscosity Index, ASTM D 2270	>110	>110	>110
Flash Point, ASTM D 92, COC, °C/°F	>250/482	>250/482	>250/482
Fire Point, ASTM D 92, COC, °C/°F	>290/554	>290/554	>290/554
Auto Ignition Temperature, °C/°F	>400/752	>400/752	>400/752
Pour Point, ASTM D 97, °C/°F	-18/-0.4	-18/-0.4	-18/-0.4
Conradson Carbon Residue, ASTM D189 wt. %	<0.1	<0.1	<0.1
Scardiameter, Fourball, ASTM D4172-20, mm	0.73	0.72	0.72

\*Subject to usual manufacturing tolerances

### Nexus LS Series

20 Mar 2024

Nexus, the Nexus logo, and related marks are trademarks of Nexus Limited, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Nexus or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.